



SolSafe[®] 245 is your ultimate solvent for industrial and precision cleaning.

SolSafe[®] 245 is the **ultimate solvent for industrial and precision parts cleaning** in manual hand-wipe applications, parts washers, dip tanks, and ultrasonic cleaners. It effectively removes oil, grease, asphalt, bitumen, and the toughest hydrocarbon contaminants without leaving a residue.

SolSafe 245's proprietary **full-strength** formulation is **non-hazardous, partially biodegradable, and non-toxic** without compromising effectiveness. It is an excellent replacement for MEK, acetone, xylene, diesel, and other hazardous solvents for many industrial applications.

SolSafe 245 also **lowers total cleaning cost** while keeping your employees **safer and protecting the environment**. The multi-purpose formulation helps **reduce your inventory** by replacing other harsh solvents, has a bath life

in immersion systems up to six times longer than mineral spirits, and the lower evaporation rate lowers the amount of SolSafe 245 needed for cleaning / degreasing.

Non-Toxic
Residue Free
Non-Chlorinated
Non-Hazardous
High Flash Point Formula
Non-Aqueous
Replaces Hazardous Solvents
Fresh Scent

AVAILABLE PRODUCTS

Item #BF1024 - 1 Gallon Can (4/cs)

Item #BF1025 - 5 Gallon Pail

Item #BF1026 - 55 Gallon Drum

Item #BF1029 - 275 Gallon Tote

APPLICATIONS

- Metal Parts Degreasing and Cleaning
- Surface Preparation Prior to Painting
- Electrical Parts Degreasing and Cleaning
- Removing Adhesive Residues
- Removal of All Heavy Hydrocarbon Fouling
- Cleaning / Degreasing Without Water



A WHOLLY OWNED
SUBSIDIARY OF



Replacing hazardous solvents without compromising effectiveness.

BioChem Systems
480 Wildwood Forest • Suite 400
Spring, Texas 77380
cservice@biochemsys.com
800-777-7870

DIRECTIONS

1. Remove all loose dirt and soil prior to cleaning.
2. Apply SolSafe[®] 245 directly to the surface to be cleaned.
3. Let penetrate for 30 seconds to two minutes.
4. Wipe dry as needed. Drying process may be accelerated by heating parts with warm, dry air. Water rinse is not required.

NOTE: SolSafe is highly effective for parts washing applications and manual cleaning.

Item #	BF1024, BF1025, BF1026, BF1029
Physical State:	Liquid
Net Contents:	1 gal, 5 gal, 55 gal, 275 gal
Container Types and Weights:	Steel Can - 1 gal - 8 lbs
	Steel Pail - 5 gal - 40 lbs
	Steel Drum - 55 gal - 430 lbs
	Tote - 275 gal - 2075 lbs
DOT Shipping Name	NOT REGULATED
Exemption	49 CFR 173.120 and 173.150
	< 119 Gallons

Scent:	Light Clean Scent, Solvent
Color:	Clear / Colorless
Flash Point:	145°F (62.7°C)
Base Type:	Petroleum
Solvency/KB	106
Dielectric Strength:	53,600 v/cm
VOC Content:	840 g/L
pH:	N/A
Relative Evaporation Rate:	NA
Relative Density	0.84
Restricted from Sale:	None
California Prop 65 Warning:	None

DANGER: Combustible liquid. May be fatal if swallowed and enters airways.

PREVENTION: Do not handle until all safety precautions have been read and understood. Keep away from heat, hot surfaces, sparks, open flames, and other ignition sources. No smoking. Wear eye protection, face protection, protective clothing, protective gloves.

RESPONSE: IF SWALLOWED: Immediately call a poison center or doctor / physician. Do NOT induce vomiting. In case of fire: Use carbon dioxide (CO₂), Foam, dry chemical, dry extinguishing powder to extinguish.

STORAGE: Store locked up in a cool, well-ventilated place.

DISPOSAL: Dispose of contents / container to hazardous or special waste collection point, in accordance with local, regional, national and / or international regulation.

EMERGENCY TELEPHONE NUMBER


PERS: (800) 633-8253

KEEP OUT OF REACH OF CHILDREN

FOR INDUSTRIAL USE ONLY



A WHOLLY OWNED
SUBSIDIARY OF 

 Replacing hazardous solvents without compromising effectiveness.

BioChem Systems
480 Wildwood Forest • Suite 400
Spring, Texas 77380
cservice@biochemsys.com
800-777-7870