

Tarpedo®

Destroys Coal Tar Sealer!



Tarpedo® quickly and effectively dissolves ready-mix and concentrated coal tar sealers.

Tarpedo® was formulated to **quickly and safely dissolve coal tar pavement sealers and cut cleaning time**, so you can focus on more important things. In as little as 30 seconds after application, Tarpedo starts dissolving the toughest coal tar sealer residue.

Tarpedo is **safe for workers and the environment**. It is partially biodegradable and has minimal toxicity to reduce environmental impact and make it friendlier for users.

Tarpedo is the perfect replacement for more hazardous and toxic solvents used

in the paving industry. It's high flash point also makes it **safer to use and non-hazardous**.

**Non-Hazardous
High Flash Point Formula
Non-Chlorinated
Partially Biodegradable
Rinses Easily with Water**

AVAILABLE PRODUCTS

Item #BF2601 - 1 Gallon Can (4/cs)

Item #BF2605 - 5 Gallon Pail

Item #BF2655 - 55 Gallon Drum

APPLICATIONS

- Asphalt paving equipment and tools cleaning
- Roofing equipment and tools cleaning
- Removal of heavy hydrocarbon fouling
- Exterior tank cleaning



A WHOLLY OWNED
SUBSIDIARY OF



Replacing hazardous solvents without compromising effectiveness.

BioChem Systems
480 Wildwood Forest • Suite 400
Spring, Texas 77380
cservice@biochemsys.com
800-777-7870

DIRECTIONS

Use full strength to remove ready mix and concentrated coal tar sealers, asphalt, adhesives, grease, oil and other tough contaminants.

1. Apply Tarpedo® directly to surface to be cleaned.
2. Use cloth or rag to wipe surface clean.
3. Rinse thoroughly with water.
4. Repeat as needed for heavy deposits.

CAUTION: Product may damage surfaces like automobile headlights and taillights. If product is sprayed on these surfaces, rinse immediately with water.

*Protect plastic (Lexan™), rubber, waxed and other similar vehicle surfaces from overspray.

Item #	BF2601, BF2605, BF2655
Physical State:	Liquid
Net Contents:	1 gal, 5 gal, 55 gal
Container Types and Weights:	Steel Can - 1 gal - 9.25 lbs
	Steel Pail - 5 gal - 44.5 lbs
	Steel Drum - 55 gal - 432.5 lbs

Scent:	Mothballs
Color:	Colorless / Slightly Yellow
Flash Point:	145°F (62.7°C)
Base Type:	Petroleum
Solvency/KB:	Not Measured
VOC Content:	100%
Relative Density:	0.9 g/m ³
Restricted from Sale:	None
California Prop 65 Warning:	Naphthalene

DANGER: Flammable liquid and vapor. May be fatal if swallowed and enters airways. Suspected of causing cancer. Toxic to aquatic life with long lasting effects.

PREVENTION: Do not handle until all safety precautions have been read and understood. Obtain special instructions before use. Keep away from heat, hot surfaces, sparks, open flames, and other ignition sources. No smoking. Use explosion-proof electrical / ventilating / lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Avoid release into the environment. Wear eye protection, face protection, protective clothing, protective gloves. Ground / bond container and receiving equipment.

RESPONSE: IF SWALLOWED: Immediately call a doctor or a poison center. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water / shower. Do NOT Induce vomiting. If exposed or concerned: get medical advice / attention. In case of fire: Use media other than water to extinguish. Collect spillage.

STORAGE: Keep container tightly closed. Store locked up in a cool, well-ventilated place.

DISPOSAL: Dispose of contents / container to a licensed hazardous-waste disposal contractor or collection site except for empty clean containers which can be disposed of as non-hazardous waste.

EMERGENCY TELEPHONE NUMBER PERS:
(800) 633-8253



WARNING: This product can expose you to Diethanolamine, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov


**KEEP OUT OF REACH OF CHILDREN
FOR INDUSTRIAL USE ONLY**



06122024



A WHOLLY OWNED
SUBSIDIARY OF



BioChem Systems
480 Wildwood Forest • Suite 400
Spring, Texas 77380
cservice@biochemsys.com
800-777-7870